Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) An apparatus comprising:

an averaging circuit adapted to provide an averaged channel estimate by performing a time domain averaging and frequency domain averaging on one or more received inputs; ~~and~~

an equalizer to equalize a received multicarrier symbol based on the averaged channel estimate; and

a coarse channel estimator to generate a coarse channel estimate to be input to the averaging circuit, the coarse channel estimator adapted to generate a coarse channel estimate as the received symbol divided by a replica of a transmitted symbol, per subcarrier.

2. (Original) The apparatus of claim 1 wherein the averaging circuit is adapted to provide an averaged channel estimate by performing a time domain averaging and frequency domain averaging on one or more received channel estimates.

3. (Original) The apparatus of claim 1 wherein the averaging circuit comprises:

Appl. No. 10/750,064

Response Dated May 15, 2007

Reply to Office Action of February 15, 2007

Docket No.: 1020.P16742

Examiner: File, Erin M.

TC/A.U. 2611

a time domain averaging block adapted to perform time domain averaging on a

plurality of received channel estimates to generate a time domain averaged channel

estimate on a per subcarrier basis;

and a frequency domain averaging block adapted to perform frequency domain

averaging on a received time domain averaged channel estimate.

4. (Original) The apparatus of claim 3 wherein the frequency domain averaging

block generates frequency domain averaged channel estimates that are used to update

coefficients of the equalizer.

5. (Original) The apparatus of claim 3 wherein the time domain averaging block is

adapted to perform time domain averaging on a plurality of received channel estimates to

generate a time domain averaged channel estimate on a per subcarrier basis using a

moving average.

6. (Original) The apparatus of claim 3 wherein the time domain averaging block is

adapted to perform time domain averaging on a plurality of received channel estimates to

generate a time domain averaged channel estimate on a per subcarrier basis using block

averaging.

7. (Canceled).

8. (Canceled).

Appl. No. 10/750,064
Response Dated May 15, 2007
Reply to Office Action of February 15, 2007

Docket No.: 1020.P16742
Examiner: File, Erin M.
TC/A.U. 2611

9. (Original) The apparatus of claim 1 wherein the equalizer comprises an adaptive equalizer.

10. (Original) The apparatus of claim 1 wherein the multicarrier symbol comprises an OFDM symbol.

11. (Currently Amended) An apparatus comprising:

an equalizer to equalize a received symbol based on a fine channel estimate;

a mapping block to provide a replica of a transmitted symbol;

a coarse channel estimator to receive a symbol replica from the mapping block and a corresponding received symbol, the coarse channel estimator to generate a coarse channel estimate as the received symbol divided by the replica of a transmitted symbol, per subcarrier; and

an averaging circuit adapted to perform time domain averaging on a plurality of coarse channel estimates to generate a time domain averaged channel estimate, and to perform frequency domain averaging on the time domain averaged channel estimate to generate the fine channel estimate.

12. (Original) The apparatus of claim 11 wherein the averaging circuit comprises a time domain averaging block and a frequency domain averaging block.

13. (Original) The apparatus of claim 11 wherein the received symbol comprises a multicarrier symbol, and the replica symbol comprises a replica of a corresponding transmitted multicarrier symbol.

14. (Original) The apparatus of claim 13 wherein the received multicarrier symbol comprises an OFDM symbol.

15. (Currently Amended) A method comprising:

performing a time domain averaging on one or more received inputs to generate a time domain averaged channel estimate on a per subcarrier basis;

performing a frequency domain averaging on the time domain averaged channel estimate to generate a fine channel estimate; ~~and~~

updating equalizer coefficients based upon the fine channel estimate; and

generating a coarse channel estimate by dividing a received multicarrier symbol by a generated replica of the corresponding transmitted multicarrier symbol.

16. (Original) The method of claim 15 wherein the performing a time domain averaging comprises:

~~generating a coarse channel estimate based on a received multicarrier symbol and a generated replica of the corresponding transmitted multicarrier symbol; and~~

performing a time domain averaging on a plurality of coarse channel estimates on a per subcarrier basis to generate a time domain averaged channel estimate.

Appl. No. 10/750,064
Response Dated May 15, 2007
Reply to Office Action of February 15, 2007

Docket No.: 1020.P16742
Examiner: File, Erin M.
TC/A.U. 2611

17. (Canceled).

18. (Currently Amended) A method comprising:

calculating an initial channel estimate based upon one or more received training

symbols;

setting equalizer coefficients based upon the initial channel estimate; performing

both time domain averaging and frequency domain averaging on a subsequent calculated

channel estimate to generate an averaged channel estimate;

generating a coarse channel estimate as a received symbol divided by a replica of

a transmitted symbol, per subcarrier; and

updating the equalizer coefficients based upon the averaged channel estimate.